(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 18 January 2001 (18.01.2001)

PCT

(10) International Publication Number WO 01/03954 A1

(51) International Patent Classification⁷: 9/18, 9/22, 1/00

B60C 11/00.

(21) International Application Number: PCT/EP00/06357

(22) International Filing Date: 4 July 2000 (04.07.2000)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

99202260.8 60/145,976 9 July 1999 (09.07.1999) EP 29 July 1999 (29.07.1999) US

- (71) Applicant (for all designated States except US): PIRELLI PNEUMATICI SPA [IT/IT]: Viale Sarca 222, I-20126 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): NAHMIAS NANNI, Marco [IT/IT]; Via della Moscova, 44/1, I-20121 Milano (IT). SERRA, Antonio [IT/IT]; Via Mantova 59 int. 49, I-16138 Genova (IT). BRUNACCI, Antonio [IT/IT]: 4, Rue de Primeveres, L-2351 Luxembourg (LU).


- (74) Agents: FERRONI, Filippo et al.; Dragotti & Associati Srl, Galleria San Babila 4/C, I-20122 Milano (IT).
- (81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS. JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HIGH PERFORMANCE TYRE WITH TREAD BAND HAVING AN ANISOTROPIC UNDERLAYER STABLE UPON TEMPERATURE VARIATION



(57) Abstract: The invention relates to a high performance tyre which has a structure consisting of the radial carcass (3) with, mounted on it, in a position increasingly towards the outside, one or more belt layers (7) and a reinforcing layer with a nylon cord (8) spirally wound around the belt. Advantageously, the tread band of the tyre is formed by an underlayer (11) and an external layer (12) arranged one upon the other, the former having elasticity and/or hardness characteristics which remain substantially unvaried between 20 °C and 110 °C: in this way the tyre is able to ensure an excellent performance even at the high speeds for which it is designed and that may cause a substantial increase in the temperature of the rubber compound.

954 A1